



Lightweight, pro-grade cylinders for CO2 or compressed air



FEATURES

- Manufactured to specifications: DOT 3AL, TC 3ALM, EN1975
- Standard 5/8" - 18 UNF thread size
- Cylinders finished with gloss black powder coating
- Seamless, high-strength aluminum 6061-T6 alloy
- Retest required every 5 years
- Inquire for custom labeling
- Valve installation available

SPECIFICATIONS

Size	Service pressure	CO2 capacity		Air capacity		Finished length		Outer diameter		Cylinder weight	
	PSI	LBS	KGS	CUBIC FT	LITERS	IN	MM	IN	MM	LBS	KGS
9 oz thin	1,800	0.59	0.26	N/A	N/A	9.38	283.13	2.13	53.98	0.67	0.31
9 oz	1,800	0.65	0.29	N/A	N/A	8.17	207.52	2.53	64.26	0.97	0.44
12 oz	1,800	0.77	0.35	N/A	N/A	9.42	239.27	2.53	64.26	1.11	0.50
16 oz	1,800	1.05	0.48	N/A	N/A	8.13	206.38	3.19	80.90	1.58	0.72
20 oz	1,800	1.30	0.59	N/A	N/A	9.38	238.13	3.19	80.90	1.52	0.69
48 oz	3,000	N/A	N/A	5.43	153.72	8.54	216.92	3.59	91.19	2.80	1.27
72 oz	3,000	N/A	N/A	8.52	241.27	9.38	238.13	4.21	106.93	3.45	1.56